

# SFFfg 4001

## Performance



|                                 |                                             |
|---------------------------------|---------------------------------------------|
| Gross/net capacity              | 316/242 l                                   |
| Ext. dimensions in mm (w/d/h)   | 597/654/1884                                |
| Int. dimensions in mm (w/d/h)   | 403/402/1588                                |
| Energy consumption in 365 days  | 384 kWh                                     |
| Ambient temperature range       | +10 °C to +35 °C                            |
| Heat output                     | 529                                         |
| Refrigerant                     | R 290                                       |
| Noise output                    | 49 dB(A)                                    |
| Frequency / voltage             | 50 Hz / 220-240 V~                          |
| Cooling system                  | static                                      |
| Defrosting                      | manual                                      |
| Temperature range               | -9 °C to -30 °C                             |
| Gradient / max. fluctuation     | 5.2 °C / 2.4 °C                             |
| Housing material/colour         | steel / white                               |
| Door material                   | steel                                       |
| Liner Material                  | commercial grade moulded polystyrol         |
| Type of Control                 | Monochrome display, touch buttons           |
| Alarm in case of malfunction    | visual and audible                          |
| Power failure alarm             | when mains power return                     |
| volt-free alarm contact         | yes                                         |
| Connectivity type               | SmartModule                                 |
| Connectivity solution           | Retrofittable                               |
| Interface                       | WLAN/LAN (optional)                         |
| Adjustable Shelving             | 5                                           |
| Shelf material                  | glass                                       |
| Usable shelf area in mm (w / d) | 403 / 402                                   |
| Shelf loading                   | 40 kg                                       |
| Maximum total load              | 270 kg                                      |
| Handle                          | Antimicrobial handle with opening mechanism |
| Type of lock                    | mechanical                                  |
| Door hinges                     | right, reversible on site                   |
| Gross/net weight                | 82/76 kg                                    |
| EAN-Nr.                         | 9005382246733                               |